

Information requirements for comfort chillers

EWFH470TZXSD1					
Outdoor side heat exchanger of chiller		Air			
Indoor side heat exchanger of chiller		Water			
Type		Inverter			
Driver of compressor		Electric			
Item	Symbol	Value	Item	Symbol	Value
Rated cooling capacity	Prated,c	460.8 kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	245.6 %
Declared cooling capacity for part load at given outdoor temperatures T_j and indoor 27°/19°C (dry/wet bulb)		Declared energy efficiency ration or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T_j			
$T_j = +35^\circ\text{C}$	Pdc	460.8 kW	$T_j = +35^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	3.2
$T_j = +30^\circ\text{C}$	Pdc	334.0 kW	$T_j = +30^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	4.7
$T_j = +25^\circ\text{C}$	Pdc	214.2 kW	$T_j = +25^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	6.7
$T_j = +20^\circ\text{C}$	Pdc	96.8 kW	$T_j = +20^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	10.3
Degradation coefficient for air conditioners		Cdc		0.9	

Power consumption in modes other than 'active mode'

Off mode	POFF	0.000 kW	Crankcase heater mode	PCK	0.000 kW
Thermostat-off mode	PTO	0.177 kW	Standby mode	PSB	0.050 kW

Other items

Capacity control	Variable
Sound power level, outdoor	LWA
Emissions of nitrogen oxides (if applicable)	NOx
GWP of the refrigerant	1.4 kg CO2eq (100 years)
For air-to-water comfort chillers: Air flow rate, outdoor measured	179676 m ³ /h
For water/brine-to water chillers: Rated brine or water flow rate, outdoor side heat exchanger	-
Standard rating conditions used:	Low Temp Application
Contact details	Daikin Applied Europe S.p.A. Via Piani di Santa Maria, 72 00072 Ariccia Roma

