

## Information requirements for comfort chillers

EWFS670TZXSD2					
Outdoor side heat exchanger of chiller					Air
Indoor side heat exchanger of chiller					Water
Type					Inverter
Driver of compressor					Electric
Item	Symbol	Value	Item	Symbol	Value
Rated cooling capacity	Prated,c	664.2 kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	216.6 %
Declared cooling capacity for part load at given outdoor temperatures $T_j$ and indoor 27°/19°C (dry/wet bulb)			Declared energy efficiency ration or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures $T_j$		
$T_j = +35^\circ\text{C}$	Pdc	664.2 kW	$T_j = +35^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	3.0
$T_j = +30^\circ\text{C}$	Pdc	491.9 kW	$T_j = +30^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	4.3
$T_j = +25^\circ\text{C}$	Pdc	309.1 kW	$T_j = +25^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	6.0
$T_j = +20^\circ\text{C}$	Pdc	140.7 kW	$T_j = +20^\circ\text{C}$	EERd or GUEc,bin/AEFc,bin	8.2
Degradation coefficient for air conditioners			Cdc		0.9

### Power consumption in modes other than 'active mode'

Off mode	POFF	0.000 kW	Crankcase heater mode	PCK	0.000 kW
Thermostat-off mode	PTO	0.115 kW	Standby mode	PSB	0.100 kW

### Other items

Capacity control	Variable
Sound power level, outdoor	LWA
Emissions of nitrogen oxides (if applicable)	NOx
GWP of the refrigerant	629.5 kg CO2eq (100 years)
For air-to-water comfort chillers: Air flow rate, outdoor measured	251568 m <sup>3</sup> /h
For water/brine-to water chillers: Rated brine or water flow rate, outdoor side heat echanger	-
Standard rating conditions used:	Low Temp Application
Contact details	Daikin Applied Europe S.p.A. Via Piani di Santa Maria, 72   00072   Ariccia   Roma

